





Bisphenol A bis(Diphenyl Phosphate) (BDP)



Description Product Name : Bisphenol A bis(Diphenyl Phosphate) (BDP)

> Equivalent Name : Chemtura Reofos BAPP; Supresta Fyrolflex BDP; Albemarle NcendX P-30

Cas No. : 5945-33-5 or 181028-79-5

Molecular Weight : 692.6

Application

BDP a halogen-free bisphosphate flame retardant used in engineered resins, and its superiority is demonstrated in low volatility, excellent hydrolytic stability, and high thermal stability that can tolerate high processing temperature required for engineered resins. It is recommended for use in PC/ABS, mPPO, epoxy resins .

Typical Properties

Appearance	Colorless Transparent Liquid.
Color APHA	80 max.
N=1 content %	80-89
Phosphorus content (Theory) %	8.9
TPP content(wt.) %	3.0 max.
IPP content(wt.) %	
Phenol content ppm	500 max.
Acidity(mg KOH/g)	
Water content (wt.) %	
Density(25 °C ,g/cm³) Dynamic Viscosity (40°C ,mPa·s)	
Dynamic Viscosity (40°C ,mPa·s)	
TGA	
5% weight loss	371°C
10% weight loss	397°C
50% weight loss	444°C

These properties are typical but do not constitute a specification either in part or as a whole. Specification data is available on request from sales, customer service or customer technical service.

Shipping Information

Transportation classification: not regulated for transportation.

Packing: 250kg / drum.4Drums / pallet. 20mt/20'FCL.

More information **Please Contact Us**

Oceanchem Group Limited

Tel: 0086 536 8596048 Fax: 0086 536 8596047

E-mail: sales@oceanchem-group.com; oceanchem@126.com

☑REACH